



(Reference Photo)

EXTERNAL DIMENSIONS

Length(mm)	7042	
Width(mm)	2500	
Height(mm)(empty)	3980	
Wheel base(mm)	3200+1400	
Wheel track(mm)	Front	2041
	Rear	1842
Min ground clearance(mm)	257	
Approach angle(°)	19	
Departure angle(°)	22	
Front overhang(mm)	1492	

FEATURES

- Reliable MC13 engine with 540Hp and 2500 High Torque.
- 12 Speed ZF AMT gearbox smoothly
- Luxury roomy Cab /Top Cooler/ ISRI Ventilated heated seat/20L Refrigerator/LED Light /Voith Retarder as standard.
- EBS/ACC/AEBS/HAS/FCWS/WABCO Radar/ Quadrangle camera.
- Differential locks and cross locks for when the going gets tough.
- Alloy rim/air tank/fuel tank/Air suspension to reduce tare weight.
- ZF steering pump /LCD Color display/Knorr brake control/Voss connector/JOST fifth wheel.
- 800L+370L dual fuel tank/90L AdBlue tank
- Fully complied with Australia Design Rules.

WEIGHTS

Max load of two axles (kg)	Front	7000
GCM (kg)	Rear	18000 90000

CAPABILITY

Max speed(km/h)	100
Min turning diameter (m)	15.5
Max climb gradient (%)	35
Fuel tank (L)	600L+380L

CABIN

Model	G7S-E
Sits	2
Turning radius (mm)	3040

ENGINE

Model	MC13.54-61
Displacement (L)	12.419
Power rating kW/(r/min)	397/1900
Max torque Nm/(r/min)	2500/1050-1350

CLUTCH

Model	CH430-25 diaphragm
Operation Mode	Electrically controlled operating with air

TRANSMISSION

Model	AMT -ZF 12TX2621TD
Forward gear ratio	16.688, 12.924, 9.926, 7.688, 5.895, 4.656, 3.655, 2.831, 2.174, 1.684, 1.291, 1.00
Reverse gear ratio	15.537, 12.033
Reverse gear ratio	

FRAME

Model	Ladder frame
Main beam cross-section (mm)	270x85x8
Width of frame Assembly(mm)	Front 942 Rear 762

DRIVING AXLE

Redactor ratio	Ratio	3.08
Differential lock	Optio	Diff lock+ cross lock

FRONT AXLE

Model	VPD71DS
-------	---------

SUSPENSION

Front	Model	Non-independent
	Number	3 leaf parabolic
Rear	Model	Non-independent
	Number	8 air bag

STEERING GEAR

Model	Ball circl
Ratio	22.2-26.2
Max pressure of pump (kPa)	18300
Steering way	Recirculating ball

BRAKING SYSTEM

Working pressure (kPa)	1000
Drive braking type	Dual circuit
Brake power adjust type	EBS-ESC-EBL-ASR
Parking brake type	Spring stored energy air cut brake
Assistant brake typ	FVB

ELECTRICS

Circuit type	double, control positive pole
Voltage (V)	24
Generator power (kW)	2.0
Accumulator voltage / capacity(V/Ah)	2x12/240

EXTRAS

Trailer brakes EBS to rear	Included
Sun visor, side skirts	Included
Retarder	INTARD3(standard)

